

### STA-RITE DIRECT REPLACEMENT SPA MOTORS

**NEW!**

**Features:**

- Open Construction
- Rigid Base
- Sealed Ball Bearing
- Threaded Shaft
- Thru-Bolt Mount
- 50° C Ambient
- 1.0 Service Factor
- 2-Speed (Capacitor Start Low Speed, PSC High Speed)



Replacement Motor for Dimension One, Hydroquip, GPM Industries, Hawkeye, Marquis and Master Spas

### Sta-Rite Direct Replacement Spa Motors

HP	RPM	Volts	Amps	Frame	Stock Number	Insulation Class	Approx. "AG"	Dim. "BX"	Notes
1.0-.12	3450/1725	115	10.4/3.6	56Z	<b>SDS1102</b>	B	10.30	8.85	
1.5-.19	3450/1725	230	7.2/2.4	56Z	<b>SDS1152</b>	F	10.79	9.34	
2.0-.25	3450/1725	230	8.5/3.0	56Z	<b>SDS1202</b>	F	11.42	9.98	
2.5-.25	3450/1725	230	10.7/3.0	56Z	<b>SDS1252</b>	F	10.67	9.23	
3.0-.38	3450/1725	230	12.0/3.7	56Z	<b>SDS1302</b>	F	10.92	9.48	

**Note:**

When crossing to an original equipment A.O. Smith Motor, use the Quick Cross Reference table. Find the amps and model number of the OEM motor on the motor nameplate. Find the equivalent amps and model number on the Quick Cross Reference table below. The replacement is the stock number listed in the "Use" column. The horsepower and service factor may not be the same, but the motors are the same.

**QUICK CROSS REFERENCE BY AMPS AND MOTOR MODEL NUMBER**

Name Plate Amps	Name Plate Model No.	Use Stock No.
10.4/3.6	K48L2A1	SDS1102
7.2/2.4	K48M2A4	SDS1152
8.5/3.0	K48N2A5	SDS1202
10.7/3.0	K48N2A4C2	SDS1252
12.0/3.7	K48P2A1	SDS1302

**NOW AVAILABLE!**  
**FAX OR PHONE YOUR ORDER TODAY!**

Distribution Services  
531 North Fourth Street  
Tipp City, OH 45371

(800) 672-6495  
Fax: (800) 468-2062  
www.aosmithmotors.com