

New!

REPLACEMENT PUMP MOTORS For Hayward TriStar™ Pumps




Features:

- 303 Stainless Steel Shaft
- 60°C Ambient
- Automatic Protector
- Ball Bearing
- Capacitor Start/Capacitor Run
- Class F Insulation
- Energy Efficient
- Open Drip Proof
- Single Phase

Single Speed - "1081" Capacitor Start/Capacitor Run - High Efficiency - Square Flange - Full Rate

HP	RPM	Volts	Amps	Service Factor	Frame	Stock Number	Shaft	Overload Protector	"C" Dim	Industry Number	Notes
1/2	3450	115/208-230	8.6/5.0-4.30	1.99	56Y	HSQ1052	Threaded	Auto	12.8	SP3205Z1BE	NEW!
3/4	3450	115/208-230	11.6/7.0-5.8	1.85	56Y	HSQ1072	Threaded	Auto	13.1	SP3207Z1BE	NEW!
1	3450	115/208-230	15.0/8.8-7.5	1.85	56Y	HSQ1102	Threaded	Auto	13.4	SP3210Z1BE	NEW!
1-1/2	3450	115/208-230	20.0/12.0-10.0	1.60	56Y	HSQ1152	Threaded	Auto	13.8	SP3215Z1BE	NEW!
2	3450	208-230	12.0-11.0	1.35	56Y	HSQ1202	Threaded	Auto	14.1	SP3220Z1BE	NEW!



Important:

- Total output (HP x service factor) of replacement motor must equal or exceed motor being replaced.
- The pool motors on this page are **NOT equipped with a Safety Vacuum Release System (SVRS)**. SVRS helps prevent drowning due to body entrapment on underwater drains. In some pool configurations, if a person's body covers the drain, the person can be trapped by suction. The SVRS turns off the pump if this occurs.

⚠ WARNING Depending on your pool configuration, a SVRS may be required to meet local, state, and federal requirements.

**NOW AVAILABLE!
FAX OR PHONE YOUR ORDER TODAY!**

Divisional Headquarters
A. O. Smith Electrical Products Company
531 North Fourth Street
Tipp City, OH 45371
A DIVISION OF A. O. SMITH CORPORATION

Distribution Services
1325 Heil Quaker Road
LaVergne, TN 37086
Phone: (866) 887-5216
Fax: (800) 468-2062
www.aosmithmotors.com